

IMSA TECHNICAL BULLETIN IWSC #22-10

To: All IMSA WeatherTech SportsCar Competitors
From: IMSA Competition
Date: January 25, 2022
Re: IMSA Rolex 24 At Daytona BoP

One Daytona Blvd.
Daytona Beach, FL
32114
: +1 (386) 310-60

In accordance with Attachment 2 of the IMSA WeatherTech SportsCar Championship SSR, the following Balance of Performance values are set for the indicated Car Models. The column listed as current is the current specification after any adjustment is applied and thus the required specification for the Event. These decisions come into immediate effect and are applicable until further notice.

DPI		Vehicles		Mass		Engine					Aero	Fuel				Notes		
Manufacturer		Minimum No Fuel/Driver (kg)		Make	Volume (L)	Turbo/NA	Restrictor Diameter (mm)			Average Power Delta (kW)	Maximum RPM	Configuration	Type	Declared Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)	
		adj	current				qty.	adj	current	adj	current			λ	adj	current		
Acura	ARX-05		930	Acura	3.5	Turbo					7050	See Table	E20	0.89		78.0	30.0	
Cadillac	DPI-V.R		950	Cadillac	5.5	NA	2		32.2		7600	See Table	E20	0.90		70.0	30.0	

* Aero configuration is defined via the Aero Configuration table on the following page.

Acura ARX-05

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.467
3200		1.467
3600		1.608
4000		1.725
4400		1.769
4800		1.769
5200		1.769
5600		1.787
6000		1.783
6200		1.773
6400		1.758
6600		1.758
6800		1.733
7050		1.701
7550		1.637
7650		1.000



Technical Bulletin

DPI		DPI AERODYNAMIC CONFIGURATIONS	FRONT AERODYNAMIC CONFIGURATIONS			REAR AERODYNAMIC CONFIGURATIONS								
			Optional front aerodynamic configurations are independent.			Optional rear aerodynamic configurations must be used as a complete package; mixing of parts/components is forbidden.								
Manufacturer		Dive Planes	Packers / Inserts	Other	Option	Tail Wicker		Rear Wing Assembly		Rear Wing Flap			Rear Wing Flap Wicker	
Permitted Options		Permitted Configurations	Permitted Options		Type	Minimum Height	Type	Minimum Angle / Position	Type	Position	Minimum Angle	Span	Minimum Height	
					mm	mm		degrees			degrees	mm	mm	
Acura	ARX-05	Per Technical Credential	Per Technical Credential	Per Technical Credential	OPTION 1	Per Technical Credential [IMSA]	16.0	Per Technical Credential [IMSA]	10.7	Sprint As-Homologated [FIA]	N/A	29.6	Removed	
		Lower	As-Tested [IMSA]	Acura Side Wicker										
		Double												
Cadillac	DPI-V.R	Per Technical Credential	Per Technical Credential	Per Technical Credential	OPTION 1	Per Technical Credential [IMSA]	30.0	Sprint As-Homologated [FIA]	12.5	Sprint As-Homologated [FIA]	STD	19.9	1200	5.0
		2019 HDF Lower	Splitter Outboard	Must run high downforce Side Wicker Option										
		2020 HDF Lower	Fill-in Packers											
		Double	Front Wheel Arch Packer + Lateral Wicker	Only at all times Must run Hood Opening at all times										
			Must run STD Front Fender Insert at all times	Must run a Front Fender Wicker of minimum height 10mm at all times										
		Bib Extension												

DPI		DPI AERODYNAMIC CONFIGURATIONS		REAR AERODYNAMIC CONFIGURATIONS							
				Optional rear aerodynamic configurations must be used as a complete package; mixing of parts/components is forbidden.							
Manufacturer		Option	Tail Wicker		Rear Wing Assembly		Rear Wing Flap			Rear Wing Flap Wicker	
			Type	Maximum Permitted Option	Type	Maximum Angle / Position	Type	Position	Maximum Angle	Maximum Permitted Option	
			mm	mm		degrees			degrees	Span	Height
			mm	mm		degrees			degrees	mm	mm
Acura	ARX-05	OPTION 1	Per Technical Credential [IMSA]	28.3 Per Template	Per Technical Credential [IMSA]	12.4	Sprint As-Homologated [FIA]	N/A	31.7	1800	10.0
Cadillac	DPI-V.R	OPTION 1	Per Technical Credential [IMSA]	30.0	Sprint As-Homologated [FIA]	15.0	Sprint As-Homologated [FIA]	Rotated	26.8	1200	5.0

LMP2 Vehicles		Mass		Engine			Aero	Fuel			Notes
Constructor		Minimum No Fuel/Driver (kg)		Make	Volume (L)	Maximum RPM	Configuration	Type	Total Capacity (L)		Minimum Full Refueling Time (sec)
		adj	current						adj	current	
ORECA	07		940	Gibson	4.2	8700	See Table	E20		75.0	34.0

* Aero configuration is defined via the Aero Configuration table on the following page.

LMP2 LMP2 AERODYNAMIC CONFIGURATIONS		FRONT AERODYNAMIC CONFIGURATIONS			REAR AERODYNAMIC CONFIGURATIONS										
		Optional Front Aerodynamic Configurations are Independent			Optional Rear Aerodynamic Configurations Must be Used as a Complete Package; Mixing of Parts/Components is Forbidden										
IWSC Rolex	Dive Planes	Packers / Inserts	Other	Option	Tail Wicker		Rear Wing Assembly			Rear Wing Flap			Rear Wing Flap Wicker		
Manufacturer	Permitted Options	Permitted Configurations	Permitted Options		Type	Minimum Height	Option	Type	Minimum Angle / Position	Type	Position	Minimum Angle	Span	Minimum Height	
					mm	mm			degrees			degrees	mm	mm	
ORECA	07	As-Homologated [FIA]: Lower	As-Homologated [FIA]	As-Homologated [FIA]	OPTION 1	As-Homologated [FIA]	16.3	OPTION 1	Sprint As-Homologated [FIA]	8.0 / Position 5 [Average of Left, Center, & Right measurements]	Sprint As-Homologated [FIA]	N/A	26.0	Full	10.0

LMP2 LMP2 AERODYNAMIC CONFIGURATIONS		REAR AERODYNAMIC CONFIGURATIONS									
		Optional Rear Aerodynamic Configurations Must be Used as a Complete Package; Mixing of Parts/Components is Forbidden									
		Option	Tail Wicker		Rear Wing Assembly		Rear Wing Flap			Rear Wing Flap Wicker	
Manufacturer			Type	Maximum Permitted Option	Type	Maximum Angle / Position	Type	Position	Maximum Angle	Maximum Permitted Option	
			mm	mm		degrees			degrees	Span	Height
ORECA	07	OPTION 1	Per Technical Credential [IMSA]	16.3	Sprint As-Homologated [FIA]	11.2 / Position 3 [Average of Left, Center, & Right measurements]	Sprint As-Homologated [FIA]	N/A	30.1	Full	10.0

GTD / GTD-PRO		Vehicles		Mass				Engine			Ride Height		Rear Wing		Fuel				Notes
Manufacturer		Minimum No Fuel/Driver (kg)		Restrictor Diameter (mm)			Average Power Delta (kW)	Maximum RPM		Minimum Ground Clearance (mm)		Min Angle (deg)	Max Angle (deg)	Type	Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)	
		adj	current	qty.	adj	current	adj	adj	current	adj	current				λ	adj	current		
Acura	NSX GT3	-25	1295						7500		50.0	+3.9	As Homologated	IMSA 100	0.88	+4.0	106.0	40.0	EVO
Aston Martin	Vantage AMR GT3		1320						7200		50.0	+6.0	As Homologated	IMSA 100	0.91		107.0	40.0	
BMW	M4 GT3	+10	1340						7000		50.0	-2.2	As Homologated	IMSA 100	1.10	-4.0	99.0	40.0	
Corvette	C8.R GTD	+15	1335	1		42.8			7400		50.0	+8.0	As Homologated	IMSA 100	0.88		93.0	40.0	15 mm Wicker Rear Wing Required
Ferrari	488 GT3		1330						7500		50.0	+6.0	As Homologated	IMSA 100	0.90		101.0	40.0	
Lamborghini	Huracan GT3		1305	2		37.0			8500		50.0	+6.8	As Homologated	IMSA 100	0.89		104.0	40.0	
Lexus	RC F GT3		1345	2		38.0			7200		50.0	+6.5	As Homologated	IMSA 100	0.86		105.0	40.0	
McLaren	720S GT3		1295						8000		50.0	+2.5	As Homologated	IMSA 100	0.88	+4.0	105.0	40.0	
Mercedes	AMG GT3		1350	2		34.5			7700		50.0	+0.8	As Homologated	IMSA 100	0.90		106.0	40.0	
Porsche	911 GT3 R		1300	2		38.0			9500		50.0	+2.0	As Homologated	IMSA 100	0.88		98.0	40.0	

Acura NSX GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.792
4000		1.792
4500		1.796
5000		1.840
5500		1.867
6000		1.881
6200		1.885
6300		1.895
6400		1.898
6500		1.896
6600		1.891
6700		1.880
6800		1.865
7000		1.834
7500		1.778
7800		1.000

Aston Martin AMR GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.510
4000		1.510
4250		1.549
4500		1.588
4750		1.637
5000		1.686
5250		1.721
5500		1.755
5750		1.794
6000		1.794
6250		1.794
6500		1.794
6750		1.765
7000		1.745
7200		1.745
7500		1.000

BMW M4 GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		2.058
3000		2.058
3500		2.058
4000		2.113
4500		2.179
5000		2.268
5250		2.328
5500		2.406
5750		2.494
6000		2.513
6250		2.533
6500		2.454
6750		2.363
7000		2.223
7250		2.117
7500		1.000

Ferrari 488 GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.448
4000		1.449
4500		1.488
4750		1.513
5000		1.538
5250		1.557
5500		1.575
5750		1.575
6000		1.576
6250		1.566
6500		1.555
6750		1.532
7000		1.509
7250		1.466
7500		1.423
7800		1.000

McLaren 720S GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.616
4000		1.616
4500		1.610
5000		1.604
5500		1.598
5750		1.579
6000		1.561
6250		1.533
6500		1.505
6750		1.463
7000		1.421
7250		1.389
7500		1.356
7750		1.352
8000		1.347
8300		1.000